AMENDED CLAIMS

This listing will replace all prior versions of the claims in the application.

What is claimed is:

- 1. (cancelled)
- 2 (cancelled)
- 3 (cancelled)
- 4 (cancelled)
- 5. (cancelled)
- 6. (cancelled)
- 7. (cancelled)
- 8. (cancelled)
- 9. (cancelled)
- 10. (cancelled)
- 11. (cancelled)
- 12. (cancelled)
- 13. (cancelled)
- 14. (cancelled)
- 15. (cancelled)
- 16. (cancelled)
- 17. (cancelled)
- 18. (cancelled)
- 19. (cancelled)

321-001 Amendment D filed

- 20. (cancelled)
- (currently amended) A barrier system comprising: 21.
 - a frame with a top, bottom, and two side portions which define an a) opening with an interior and exterior side;
 - a planar barrier disposed within the frame comprised of a plurality b) of strips with cutters <u>barbs</u> that is operable in the plane between an extended condition whereby the planar barrier substantially covers the opening and a retracted condition whereby the planar barrier does not substantially cover the opening;
 - a first barrier sheet attached to the interior side of the frame to cover the planar barrier; and
 - a second barrier sheet attached to the exterior side of the frame to cover the planar barrier.
- 22. (previously presented) The system of claim 21 wherein the top portion of the frame is a ceiling, the bottom portion is a floor, and the two side portions are walls.
- 23. (cancelled)
- 24. (currently amended) The system of claim 23 21 wherein the first barrier sheet is glass.

- 25. (currently amended) The system of claim 23 23 wherein the <u>first</u> barrier sheet is plastic.
- 26. (previously presented) The system of claim 21 wherein the frame is a doorway.
- 27. (cancelled)
- 28. (cancelled)
- 29. (previously presented) The system of claim 21 further comprising a retraction compartment located on the frame that can receive the planar barrier when it is in the retracted condition.
- 30. (previously presented) The system of claim 29 wherein the retraction compartment is located on the top portion of the frame.
- 31. (currently amended) A parrier system to prevent access through an opening comprising:
 - a) a frame with a top, bottom, and two side portions which define an opening with an interior and exterior side;

321-001 Amendment D filed

- b) a planar barrier disposed within the frame comprised of a plurality
 of strips with razors that is operable in the plane between an extended
 condition whereby the planar barrier substantially covers the opening and
 a retracted condition whereby the planar barrier does not substantially
 cover the opening;
- c) a first barrier sheet attached to the interior side of the frame to cover the planar barrier; and
- d) a second barrier sheet attached to the exterior side of the frame to cover the planar parrier.
- b) a planar, according barrier sheet comprising a plurality of strips with cutters barbs connected to each other with rivets;
- between an extended condition whereby the planar, accordion

 barrier sheet substantially covers the opening and a retracted

 condition whereby the planar, accordion barrier sheet does not

 substantially cover the opening.
- 32. (currently amended) The system of claim 31 wherein the planar, accordion barrier sheet folds into equal sized, flat segments when in the retracted condition.
- 33. (cancelled)

- 34. (cancelled)
- 35. (currently amended) The system of claim 34 31 wherein at least one the two barrier sheets are is glass.
- 36. (currently amended) The system of claim 31 wherein at least one the barrier sheets are is plastic, the cutters are razer.
- 37. (cancelled)
- 38. (currently amended) The system of claim 31 further comprising a retraction compartment that can receive the planar, accordion barrier sheet-when it is in the retracted condition.
- 39. (currently amended) The system of claim 33 31 further comprising a retraction compartment located on the top portion of the frame that can receive the planar, accordion barrier sheet when it is in the retracted condition.
- 40. (previously amended) A barrier system attached to an opening of a building for preventing access through the opening comprising:
 - a) a frame with an interior side and an exterior side that is defined by
 a top ceiling portion, a bottom floor portion, and two side portions;

- b) a planar barrier located between the interior and exterior sides of the frame comprised of a plurality of strips with a plurality of razors wherein the planar barrier is operable in the plane between an extended condition whereby the planar barrier substantially covers the opening and a retracted condition whereby the planar barrier does not substantially cover the opening; and
- c) a first barrier sheet attached to the interior side of the frame to cover the planar barrier; and
- d) a second barrier sheet attached to the exterior side of the frame to cover the planar barrier.